

July 2025

HYUNDAI PERFORMANCE GREASE EP2

Premium high performance Multipurpose grease. It is a NLGI 2 grease manufactured from a lithium soap and mineral soap. It contains lead-free extreme pressure additives as well as antioxidants and anti-corrosion agents to protect components and ensure good lubrication at high loads.

Specifications, Approvals & Recommendations

- HD HCE GR-E1
- NLGI 2

For a full listing of equipment approvals and recommendations, please consult your local representative.

Typical Physical Characteristics

PROPERTIES			METHOD	HYUNDAI GREASE
NLGI Consistency				2
Soap Type				Lithium
Base Oil				Mineral
Kinematic Viscosity	@40°C	cSt	IP 71 / ASTM D445	220
Kinematic Viscosity	@100°C	cSt	IP 71 / ASTM D445	19
Cone penetration, Worked	@25°C	0.1 mm	IP 50 / ASTM D217	265 - 295
Dropping Point		°C	IP 396	180

These characteristics are typical of current production.

Health, Safety & Environment

- **Health and Safety**
 - This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
 - Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Safety Data Sheet.
- **Protect the Environment**
 - Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

