

July 2025

HYUNDAI PERFORMANCE GEAR OIL

Hyundai Performance Gear Oil is formulated to protect construction equipment, meeting the needs of front and rear axles, hub casing, and differentials with limited-slip additives for enhanced reliability, efficiency, and cost savings.

Specifications, Approvals & Recommendations

- API Service Classification GL-4

For a full listing of equipment approvals and recommendations, please consult your local representative.

Typical Physical Characteristics

PROPERTIES	METHOD	HYUNDAI PERFORMANCE GEAR OIL
Kinematic Viscosity @100°C	ISO 3104	9.4 mm ² /s
Density @15°C	ISO 12185	882 kg/m ³
Pour Point	ISO 3016	-42°C
Flash Point	EN ISO 2592	220°C

These characteristics are typical of current production. Whilst future production will conform to HD Hyundai's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

- This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Safety Data Sheet.

• Protect the Environment

- Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

